

1FT x 4FT Suspended Linear w/ Uplight



Product Advantages

- Architectural suspended design, with 35% uplight, 65% downlight
- Significant saving in power consumption and costs
- Minimal maintenance costs (materials and labour)
- Minimal heat generation
- No flicker. Significant reduction in eye strain
- Engineered optic design producing even light distribution with no hot spots.
- Ideal for all applications currently using traditional fluorescent fixtures.

Description

| | |
|-----------------------|------------------------------|
| Model No. | LS14P-40K-54 |
| Actual Size | 47.24" x 11.8" x 1.06" |
| Power | 54w |
| CCT | 3000k, 3500k |
| CCT | 4000k, 5000k |
| Luminous(lm) | 4930 |
| Lighting Effect | up to 100 lm/w |
| CRI | >80 |
| Power Factor | > 0.90 |
| Light Distribution | 35% uplight 65% downlight |
| Input Voltage | 110 – 277v, 50-60Hz |
| Driver Output Voltage | 36 – 42v, 1.5A |
| Work Temp | -20°C to +50°C |
| Beam Angle | 120° |
| Dimmable | 0 – 10v and Step Dimming |
| IP Rating | Damp Rated |
| Lifespan | 50,000 Hours |
| Warranty | 7 Years |

Certifications:

