

Lumalex – 2FT X 2FT Panel



Description

Model No.	L22-35K-40 L22P-40K-27 L22P-40K-40 L22P-50K-40
Actual Size	23.7" x 23.7" x 1.09" (includes JB)
Power	27w, 40w at 110 – 277v, 42W at 347v
CCT	3500k, 4000k, 5000k
Luminous(lm)	2975 lm up to 4505 lm
Lighting Effect	up to 125lm/w
CRI	>80, >90 for 3500k High R9
Power Factor	> 0.95
Input Voltage	110 – 277v/ 347v AC, 50-60Hz
Driver Output Voltage	36v DC at 1 amp
Work Temp	-20°C to +50°C
Beam Angle	120°
Dimmable	0 – 10v and Step Dimming
IP Rating	Damp Rated
Lifespan	50,000 Hours
Warranty	7 Years

Product Advantages

- Direct Replacement for traditional fluorescent tube fixtures
- Significant saving in power consumption and costs
- Minimal maintenance costs (materials and labour)
- Minimal heat generation
- No flicker. Significant reduction in eye strain
- Engineered optic design producing even light distribution with no hot spots.
- Flat surface mount design available. Tight to any flat surface ceiling.
- Optional mounting for flat surface ceilings.

Certifications:

