

# Lumalex – 2FT X 4FT Panel



## Description

Model No.	<i>L24-35K-40 L24P-40k-40 L24P-50K-50, L24P-50K-65 L24P-50K-63-347</i>
Actual Size	<i>47.7" x 23.7" x 0.625" (1.09" with JB)</i>
Power	<i>40w, 50w, 110 – 227v, 63w, 347v</i>
CCT	<i>3500k, 4000k</i>
CCT	<i>5000k</i>
Luminous(lm)	<i>4100lm, 5225lm, 6205lm, 6300lm</i>
Lighting Effect	<i>up to 105 lm/w</i>
CRI	<i>&gt;80</i>
Power Factor	<i>&gt; 0.95</i>
Input Voltage	<i>110 – 277v/ 347v AC, 50-60Hz</i>
Driver Output Voltage	<i>27 – 42v, 1.5A</i>
Work Temp	<i>-20°C to +50°C</i>
Beam Angle	<i>120°</i>
Dimmable	<i>0 – 10v and Step Dimming</i>
IP Rating	<i>Damp Rated</i>
Lifespan	<i>50,000 Hours</i>
Warranty	<i>7 Years</i>

## Product Advantages

- Direct Replacement for traditional fluorescent tube fixtures
- Significant saving in power consumption and costs
- Minimal maintenance costs (materials and labour)
- Minimal heat generation
- No flicker. Significant reduction in eye strain
- Engineered optic design producing even light distribution with no hot spots.
- Flat surface mount design available. Fits tight to any flat surface ceiling.
- Optional mounting for flat surface ceilings.

## Certifications:

